

COLORPRINT
Digital printing material

<p>Description</p>	<p>Material specifically formulated for thermoresin, ink jet solvent and eco solvent based inks – printing and cutting systems. Polyester backing.</p>
<p>Tips</p>	<p>Certified by Roland® for VersaCamm SP-300 and Ink Jet printers using eco solvent based inks</p> <p>We suggest to let the print dry (at least 12 hours) before rolling, overlaying or heat transferring the material. We highly recommend application and washing test.</p>
<p>Application instructions</p>	<ol style="list-style-type: none"> 1) Print and cut the material 2) Let the print dry at least 12 hours. 3) Weed and remove image from backing with an hot resistant application tape. We recommend to use the Siser transparent polyester TTD 4) Heat apply following the below indicated conditions 5) Remove application tape once cold <p>Due to the many different base materials available on the market, the following heat transfer instructions are given as guideline only:</p>
<p>Temperature: Time: Pressure: Washable to:</p>	<p>150°C 10 – 15 sec. medium 50°C Max.</p>

SIZES AND COLOURS

<p>ROLLS</p>	<p>width 1,50 m.</p>	<p>length 25 m.</p>
	<p>width 0,50 m.</p>	<p>length 25 m.</p>
<p>COLOURS</p>	<p>white</p>	