

# PRODUCT INFORMATION

Mod. R&S. 05/0 Pag. 1/1

Last Updating: 10/2008

## **JETFLOCK 2**

#### Description

Jetflock 2 is a new cutting material with a polyester-flock, which can be printed with sublimation inks. **Polyester** backing.

#### **Basic Information**

Due to the many different base materials available on the market, the following heat transfer instructions are given as guideline only:

**Temperature:** 180°C

Time: 20"

Pressure: medium

Important: Time and temperature are just indicative. Kindly follow instructions for the used inks'

sublimation

### **Application Instructions**

- 1) Print and cut the material
- 2) Remove images from polyester backing
- 3) Cover with a silicon treated paper
- 4) Heat apply
- 5) Remove the silicon paper once cold

#### Suitable for

Cotton, polyester, poly-cotton blends Not suitable for treated garments

Washing: (wait 24h after the heat transfer)

40°C Max. – wash inside out - do not use bleach or other aggressive chemical agents

**Dry-cleaning:** no

Tumble drier: not advisable

N.B.: all information given in this sheet are based on our experience

We recommend to always perform a test before starting standard production

The product meets the Italian and Ue regulations relating to its proper use. This document can be subject to variations. Updated versions are available on our website <a href="www.siser.it">www.siser.it</a>. For further information, please contact our Sales Office. Thank you.





