

JETFLOCK SOLVENT

Description

Heat seal Flock material, specifically formulated for all general Solvent and Eco-Solvent printing and cutting systems.

It features a high covering power, brilliant colour reproduction and an easy handling.

Basic Information

Due to the many different base materials available on the market, the following heat transfer instructions are given as guideline only:

Temperature: 180°C

Time: 15''

Pressure: medium

Application Instructions

- 1) Print and cut the material
- 2) Let the print dry at least 2 hours before rolling, overlaying or heat transferring the material
- 3) Weed the exceeding material
- 4) Remove the image from the backing by hand and over with a silicon treated paper
- 5) Heat apply
- 6) Remove the silicon treated paper

Suitable for

Cotton, polyester, poly-cotton blends and acryl.

Not suitable for treated and dyed garments (sublimation inks)

Washing: (wait 24h after the heat transfer)

60°C Max. – wash inside out - use only mild detergent - no bleach, fabric softener or liquid detergent

Dry-cleaning : not advisable

Tumble drier : yes

N.B. : all information given in this sheet are based on our experience

We recommend to always perform a test before starting standard production

The product meets the Italian and Ue regulations relating to its proper use.

This document can be subject to variations. Updated versions are available on our website www.siser.it.

For further information, please contact our Sales Office. Thank you.

SISER s.r.l.

V.LE DELLA TECNICA n. 18 – 36100 VICENZA ITALY

TEL. +39 0444 287960 - FAX +39 0444 287959 - E-mail: info@siser.it - www.siser.it

R.E.A. VI 171856 VI – Reg. Imp. VI n. 14971 - Cap. Soc. € 103.300 i.v. – Partita IVA 01591490246

