

SUBLIPRINT

<p>Description</p>	<p>Digital printing material for ink jet solvent and eco solvent based inks – printing and cutting systems for application onto dyed garments (sublimation inks). The special formulation and processing of the material create a barrier to the dyes of the textile avoiding the sublimation bleed: decoration colour won't change along time. Polyester backing.</p>
<p>Tips</p>	<p>We highly recommend application and washing test</p>
<p>Application instructions</p>	<p>1) Print and cut the material 2) Let the print dry at least 12 hours 3) Weed and remove image from backing with an hot resistant application tape. We recommend to use the Siser transparent polyester TTD 4) Heat apply following the below indicated conditions 5) Remove application tape warm</p> <p>Due to the many different base materials available on the market, the following heat transfer instructions are given as guideline only:</p>
<p>Temperature: Time: Pressare: Washable to:</p>	<p>165°C 15 sec. minimum 30°C Max.</p>

SIZES AND COLOURS

<p>ROLLS</p>	<p>width 1,50 m.</p>	<p>length 25 m.</p>
---------------------	----------------------	---------------------

Last updating: February 2008



***PRODUCT
INFORMATION***

*Mod. R&S.05/0
Pag. 2/ 1*

COLOURS

width 0,50 m.
white

length 25 m.