

ORATAPE

LT 95 Application Tape

Technical Data Sheet

08/23

Description

Transparent, polyethylene-based mounting film with a fine-pocked finish for the transfer of die-cut and computer-cut letters and symbols.

Adhesive

Modified polyacrylate, low adhesive strength.

Area of use

This mounting film has been developed for special uses which requires an extraordinary low adhesive power.

Technical data

Thickness* (film with adhesive)	150 micron
--	------------

Weight* (film with adhesive)	105 g/m ²
-------------------------------------	----------------------

Adhesive power* (FINAT TM 1, after 20min, stainless steel)	< 1 N/25 mm
--	-------------

Tensile strength (DIN EN ISO 527)	
along	min. 25 MPa
across	min. 25 MPa

Elongation at break (DIN EN ISO 527)	
along	min. 500%
across	min. 700%

Shelf life**	1 year
---------------------	--------

Application temperature	> +10°C
--------------------------------	---------

* average ** in original packaging, at 20°C and 50% relative humidity

The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications customers should independently determine the suitability of this material for their specific purpose, prior to use.



ORAFOL Europe GmbH - Orafolstraße 2 - D 16515 Oranienburg
Telefon: +49 (0) 33 01/864 0 - Telefax: +49 (0) 33 01/864 100
E-Mail: verkauf@orafol.de - Internet: <http://www.orafol.d>